MAY 2 6 2005 U

IN THE CLAIMS

A listing of all claims and their current status in accordance with 37 C.F.R. § 1.121(c) is provided below.

1-52. (canceled)

53-59. (canceled)

60. (previously presented) A method for measuring blood oxygen saturation comprising:

emitting light from at least one light source;

detecting light, at a detector, from said light source subsequent to being scattered by tissue, the light including an infrared light spectrum, said infrared spectrum having a range useful for measuring oxygen saturation in a patient with high saturation, the detected light also including a red light spectrum, said red light spectrum having a mean wavelength between 700 and 790 nanometers; and

limiting light signals received at the detector from the light source to no more than three spectra.

61. (previously presented) The method of claim 60 further comprising: providing a red light spectrum having a mean wavelength less than 700 nanometers.

- 62. (previously presented) The method of claim 60 further comprising: emitting light in said infrared light spectrum between 805 and 940 nm.
- 63. (previously presented) A method for measuring oxygen saturation comprising: emitting light from at least one light source;

detecting light with at least one light detector after scattering by tissue;

limiting light signals received at the detector from the light source to no more than three spectra, a first spectrum including 735 nanometers at an intensity of at least 50% of the intensity of any other wavelengths in said first spectrum.

64. (previously presented) The method of claim 63 wherein a second spectrum has a mean wavelength of from 805 to 940 nm used, in conjunction with said first spectrum, for measuring oxygen saturation in a patient.

65. (withdrawn)

66. (previously presented) A method for measuring oxygen saturation comprising: emitting light from at least one light source;

detecting light from the light source with a detector after scattering by tissue;

limiting light signals received at the detector to only first and second spectra, a first spectrum having a mean wavelength in the infrared rage of from 805 to 940 nm used conventionally for measuring oxygen saturation in a patient with high blood saturation, and a

second spectrum having a mean wavelength of from 700 to 790 nm used, in conjunction with said first spectrum, for measuring oxygen saturation in a patient.

- 67. (previously presented) The method of claim 66 wherein said method is used for fetal sensing.
- 68. (previously presented) The method of claim 66 wherein said second spectrum is used for calculating oxygen saturation for saturations below 80%.
- 69. (previously presented) The method of claim 66 wherein said second spectrum is used for calculating oxygen saturation for saturations below 65%.